



## Características generales

- Fusibles Clase F.
- Tensión Nominal: 250 Vac.
- Capacidad de Ruptura: 1,5 kA.
- Características de fusión: lenta (T) y rápida(F).
- En conformidad con las normas IEC 60127- EN60127.

Corriente nominal ( A )	Tamaño 5x20		Tamaño 6x32	
	F Rápidos (Código)	T Lentos (Código)	F Rápidos (Código)	T Lentos (Código)
0,03	500006	520006		
0,04	500002	520002	504002	534002
0,05	500003	520003	504001	534001
0,063	500005	520005	504004	534004
0,08	500004	520004	504003	534003
0,1	500007	520007	504005	534005
0,125	500013	520013	504011	534011
0,16	500010	520010	504008	534008
0,20	500011	520011	504009	534009
0,25	502250	522250	503250	533250
0,315	500014	520014	504012	534012
0,4	500008	520008	504006	534006
0,5	502050	522050	503050	533050
0,63	500012	520012	504010	534010
0,8	500009	520009	504007	534007
1	502001	522001	503001	533001
1,25	500016	520016	504014	534014
1,6	500015	520015	504013	534013
2	502002	522002	503002	533002
2,5	500017	520017	504015	534015
3	502003	522003	503003	533003
3,15	500018	520018	504016	534016
4	502004	522004	503004	533004
5	502005	522005	503005	533005
6	502006	522006	503006	533006
6,3	500019	520019	504017	534017
7	502007	522007	503007	533007
8	502008	522008	503008	533008
9	502009	522009	503009	533009
10	502010	522010	503010	533010
12	502012	522012	503012	533012
15	502015	522015	503015	533015
16	502016	522016	503016	533016
20	502020	522020	503020	533020
25			503025	533025



## Bases portafusibles

Tamaño	Código	Corriente nominal	Tensión nominal	Fijación fusible
5x20	515020	6,3	250	Bayoneta
5x20	515120	6,3	250	Pinzas
6x32	516032	16	250	Bayoneta
6x32	516132	16	250	Pinzas

